

Flexovit USA Inc

SAFETY DATA SHEET

SECTION 1 - Identification of the Product and Company

1.1 Product Name Flap Wheels (Shank Mounted & Unmounted)
1.2 Product Use For light material cleaning, finishing, polishing and blending
1.3 Company Details: **Flexovit USA Inc.**
Address: 1305 Eden-Evans Center Rd.
Angola, NY 14006
Phone: 1-716-549-5100
Fax: 1-716-549-7932

SECTION 2 - Hazard Information

2.1 Precautionary statements

Wear Respirator, eye protection, and protective clothing when using product
Product will produce sparks and debris when in use, avoid using product near reactive or flammable substances or electrical equipment

2.2 Description of Hazards

Respiratory Irritant
Skin Irritant

SECTION 3 - Composition

<u>Ingredient</u>	<u>Formula</u>	<u>% Weight</u>	<u>OSHA Regulated</u>	<u>Cas #</u>
Silicon Carbide		0-30	Yes	409-21-2
Aluminum Oxide		0-30	Yes	1349-28-1
Zirconium Oxide		0-30	Yes	1314-23-4

SECTION 4-First Aid

4.1 First Aid for exposure

Dust Inhalation: Remove to fresh air, apply artificial respiration as needed. Obtain medical assistance.
Ingestion: Obtain medical assistance.
Skin contact: Obtain medical assistance.
Eye: Wash with large amounts of water. Obtain medical assistance.
Hearing: Obtain medical assistance.

4.2 Signs and Symptoms of Exposure

Acute: May cause coughing and shortness of breath
Skin abrasions
Eye irritation
Chronic: May effect breathing capacity
Elevated sound levels may be created which affect hearing

SECTION 5 - Fire Fighting Measures

- 5.1 Means Of Extinction: N/A
- 5.2 Unusual Fire or Explosion Hazards: N/A
- Flammable Properties: N/A
- 5.3 Special Fire Fighting Procedures: Backing and resin binder will burn or decompose, use respiratory protection

SECTION 6 - Accidental Release Measures

Normal clean up procedures should be used if material is released

SECTION 7- Storage, Handling and Use Procedures

- 7.1 Handling: Handle in accordance with ANSI B7.1
- 7.2 Storage: Dry area at moderate temperature and humidity

SECTION 8- Personal Protective Control Measures

8.1 Exposure limits

<u>Chemical</u>	<u>OSHA PEL</u>	<u>ACGIH TLV</u>
Silicon Carbide	15 mg/m ³	10 mg/m ³
Aluminum Oxide	15 mg/m ³	10 mg/m ³
Zirconium Oxide	15 mg/m ³	10 mg/m ³

8.2 Personal protection requirements and referrals

- Protection: Requirements and Referrals
- Respiratory: OSHA/NIOSH approved respirator. See OSHA 29 CFR 1910.134 or European Standard EN 149.
- Ventilation: Engineering Controls recommended. See ANSI Z43.1. Refer to OSHA 29 CFR 1910.94.
- Protective Gloves: Leather gloves
- Eye Protection: Protective eyewear such as safety glasses or face shield. Refer to OSHA 29 CFR 1910.133.
- Hearing Protection: Hearing protection such as approved ear muffs or ear plugs. Refer to OSHA 29 CFR 1910.95.
- Body Protection: Leather apron, chaps, or shoe coverings to shield from heavy spark showers in operation.
- Hygienic Practices: Wash with soap and water after handling and grinding.

SECTION 9- Physical/Chemical Characteristics

Boiling Point	N/A	Specific Gravity	N/A
Vapor Pressure (mm Hg.)	N/A	Melting Point	N/A
Vapor Density (AIR=1)	N/A	Evaporation Rate (Butyl Acetate=1)	N/A
Solubility in Water	N/A	Appearance	Color of fibre/ coated with abrasive material
Lower And Upper Explosion Limits			
Flammable Limits		Odor	
Flash Point		Degradation Temperature	

SECTION 10 - Stability and Reactivity Data

Stable

Hazardous Polymerization will not occur

SECTION 11 - Toxicological Data

11.1 Component information

<u>Chemical</u>	<u>Short term effects</u>	<u>Long term effects</u>	<u>Carcinogen</u>
Silicon Carbide	skin, respiratory irritation	N/A	No
Aluminum Oxide	skin, respiratory irritation	N/A	No
Zirconium Oxide	skin, respiratory irritation	N/A	No

11.2 Route(s) of Entry and symptoms of exposure

See section 4.2

Section 12-Ecological Information

No Data Available

Section 13-Disposal Considerations

Dispose in accordance to local and federal regulations

Section 14-Transport Information

Not regulated as a hazardous material for transport

Section 15-Regulatory Information

California Proposition 65: **WARNING!** You create dust when you cut, sand, drill or grind materials such as wood, paint, cement, masonry or metal. This dust often contains chemicals known to cause cancer, birth defects or other reproductive harm.

Section 16-Other Information

SDS Revision Date October 1 2023

Reason for Update Mandated Update

Preparation By: FlexOvit USA

COMPANY USE

The information and recommendations set forth herein are taken from sources and references believed to be accurate and complete as of the date hereof. However, FlexOvit USA Inc makes no expressed or implied warranty with respect to the accuracy of the information or the suitability of the recommendations, and assumes no liability to any user thereof.