# Flexovit USA Inc

# SAFETY DATA SHEET

#### **SECTION 1 - Identification of the Product and Company**

1.1 Product Name Floor Maintenance Pads (non-woven)

**1.2** Product Use Stripping, Scrubbing, Buffing, and Polishing

**1.3** Company Details: Flexovit USA Inc.

Address: 1305 Eden-Evans Center Rd.

Angola, NY 14006

Phone: 1-716-549-5100 Fax: 1-716-549-7932

# **SECTION 2 - Hazard Information**

## 2.1 Precautionary statements

Not classified as hazardous according to OSHA Hazard Communication Standard, 29 CFR 1910.1200.

No applicable hazard labels, signal words or pictograms

Dusts may cause irritation, coughing, shortness of breath. May affect breathing capacity.

Determine the hazard potential of materials being treated, abraded or polished by referring to MSDS or SDS for associated materials.

<b>SECTION 3 - Compositi</b>	on (may	y contain one	or more	of the f	ollowing	ingredients
OLOTION COMPOSIC	OII (IIIG	y contain one	01 111010 1	J. 1110 1	One wing	ii igi calci ii

Ingredient	<u>Formula</u>	% Weight	OSHA 8 hr PEL	Cas #
Aluminum Oxide		0-30%	15 mg/m <sup>3</sup>	CAS 1344-28-1
Silicon Carbide		0-30%	15 mg/m <sup>3</sup>	CAS 409-21-2
Cured Acrylic Resin		5-30%	15 mg/m <sup>3</sup>	NA
Nylon or polyester fibers		0-80%	15 mg/m <sup>3</sup>	NA
Natural Animal Fibers (hog hair)		0-10%	Not established	NA

# **SECTION 4-First Aid**

# 4.1 First Aid for exposure

Remove to fresh air, apply artificial respiration if needed. In case of eye contact, flush with large amounts of water. Obtain medical assistance if needed.

# 4.2 Signs and Symptoms of Exposure

Skin or eye irritation, coughing, shortness of breath.

## **SECTION 5 - Fire Fighting Measures**

5.1 Means Of Extinction: Water, CO2 or Dry Chemical fire extinguisher

**5.2** Unusual Fire or Explosion Hazards: None

Flammable Properties: Does not readily support combustion

5.3 Special Fire Fighting Procedures: No special procedures required

#### **SECTION 6 - Accidental Release Measures**

Not Applicable

# **SECTION 7- Storage, Handling and Use Procedures**

7.1 Handling: Standard industrial practices apply

**7.2** Storage: Keep abrasive products dry. Avoid temperature and humidity extremes.

## **SECTION 8- Personal Protective Control Measures**

#### 8.1 Exposure limits

Chemical	OSHA PEL	ACGIH TLV

Aluminum Oxide 15 mg/m<sup>3</sup> 10 mg/m<sup>3</sup>

Silicon Carbide 15 mg/m<sup>3</sup> 10 mg/m<sup>3</sup> (inhalable fraction)

Cured Urea Formaldehyde Resin15 mg/m³Not establishedNylon or polyester fibersNANot establishedAnimal fibers (hog hair)NANot established

# 8.2 Personal protection requirements and referrals

# **Respiratory Protection:**

Use NIOSH approved respirator if exposure limits are exceeded or where dust exposures are excessive. Consider the potential for exposure to components of the coatings or base material being abraded or prepared in selecting proper respiratory protection. Refer to OSHA's specific standards for lead, cadmium, which may be found in coatings and material being abraded. Selection of respiratory protection depends on the contaminant type, form and concentration. Select and use respirators in accordance with OSHA 1910.134 and prudent industrial hygiene practice.

#### Ventilation:

Use local exhaust or general ventilation as required to minimize exposure to dust and maintain levels of contaminants lower than the established threshold limit values.

### **Protective Gloves:**

Cloth, leather, or rubber gloves to protect from abrasion and other chemicals that may be used in process.

# **Eye Protection:**

Safety glasses with side sheilds or goggles are recommended.

# **Hearing Protection:**

Recommended when power tools are in use.

## **Body Protection:**

Recommended when power tools are in use.

# **Hygienic Practices:**

Use soap and water to remove dusts from person prior to eating or drinking. Protect food, drink and other consumables from dust contamination.

## **SECTION 9- Physical/Chemical Characteristics**

Boiling PointNot ApplicableSpecific GravityHeavier than waterVapor Pressure(mm Hg.)Not ApplicableMelting PointNot ApplicableVapor Density(AIR=1)Not ApplicableEvaporation Rate (Butyl Acetate= Not Applicable

Solubility in Water Appearance

Non-woven fiber mat. May or may not contain embedded

abrasive particles.

Lower And Upper Explosion LimitsNot ApplicableOdorNot ApplicableFlammable LimitsNot ApplicableDegradation TemperatureNot Established

Flash Point Not Applicable

## **SECTION 10 - Stability and Reactivity Data**

Stability: Stable

Water resistant

Incompatibility: None known.

Hazardous Decomposition Products: Dust from use could contain ingredients listed in Section 2.

Other, potentially more hazardous components may be present in the coating or material being abraded, polished or

otherwise treated.

Hazardous Polymerization: Will not occur.

#### **SECTION 11 - Toxicological Data**

## 11.1 Component information

Ingestion: None expected under normal use conditions. Swallowing large pieces may cause obstruction.

Eye: Dust may cause eye irritation. Dust or abrasive particles may cause abrasive injury to the eyes.

Skin: None expected under normal use conditions. Contact with skin may cause removal of skin (abrasions).

**Sensitization:** Not expected under normal use conditions.

**Chronic:** Long term overexposure to dust may cause lung damage, decrease in lung function. Elevated noise levels from power equipment and other machinery may result in hearing loss. A significant toxicological hazard is presented by potentially hazardous materials being removed or abraded.

Carcinogenicity: None of the components are listed as a carcinogen or potential carcinogen by OSHA, NTP or IARC.

### 11.2 Route(s) of Entry and symptoms of exposure

See section 4.2

# **Section 12-Ecological Information**

This product is not expected to be hazardous for the environment. No specific ecotoxicity data is available for this product.

#### **Section 13-Disposal Considerations**

Dispose in accordance with all applicable local, state/provincial and federal regulations.

## **Section 14-Transport Information**

DOT Hazardous Materials Description:

Proper Shipping Name: Not Regulated

**UN Number:** None

Hazard Class/Packing Group: None

Labels Required: None

# **Section 15-Regulatory Information**

SARA Section 311/312 Hazard Categories: Not Applicable

California Proposition 65: WARNING You create dust when you cut, sand, drill or grind materials such as wood, paint, cement masonry or metal. This dust often contains chemicals known to cause cancer, birth defects or other reproductive harm.

**Canadian WHMIS Classification:** Not a controlled product. This product meets the definition of a "manufactured article" under the WHMIS regulations.

## **Section 16-Other Information**

Reason for Update: October 1 2023

Reparation By: October 1 2023

Mandated Update

FlexOvit USA

## **COMPANY USE**

The information and recommendations set forth herein are taken from sources and references believed to be accurate and complete as of the date hereof. However, FlexOvit USA, Inc makes no expressed or implied warranty with respect to the accuracy of the information or the suitability of the recommendations, and assumes no liability to any user thereof.